

AIR OPERATED LOCKING DIFFERENTIAL

RD220

T6 Ranger/BT50, RR, 32 SPL

PARTS L	JIST			
ITEM#	QTY	DESCRIPTION	PART#	NOTES
1	1	FLANGE CAP KIT	027340SP	
2	1	BONDED SEAL	160702SP	
3	1	CLUTCH GEAR & WAVESPRING KIT	050906SP	
4	1	WAVESPRING	150706SP	
5	2	SHORT CROSS SHAFT	060403SP	
6	4	PINION THRUST WASHER	SEE NOTE	3
7	4	PINION GEAR	SEE NOTE	2
8	1	LONG CROSS SHAFT	060204SP	
9	1	SIDE GEAR	SEE NOTE	2
10	1	DIFFERENTIAL CASE	013040SP	
11	1	COUNTERSUNK SCREW (PK OF 2)	200213SP	
12	1	RETAINING PIN SET (PK OF 4)	120601SP	
13	1	SHIM KIT	SHK009	
14	1	SEAL HOUSING KIT	081809SP	
15	1	SEAL HOUSING O-RINGS (PK OF 2)	160207SP	1
16	*	TAPERED ROLLER BEARING	NOT SUPPLIED	
17	2	SIDE GEAR THRUST WASHER	SEE NOTE	3
18	1	SPLINED SIDE GEAR	SEE NOTE	2
19	1	SPIDER BLOCK	070201SP	
*	1	BULKHEAD FITTING KIT (BANJO TYPE)	170114	4
*	1	AIR LINE (6mm DIA X 6m LONG)	170314SP	4
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH	180209SP	
*	1	SWITCH COVER (REAR)	180211SP	
*	1	CABLE TIE (PK OF 25)	180305	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	2102220	

NOTES

- 1 For replacement O-rings use only BS136 Viton 75.
- 2 Available only as complete 6 gear set #728H171
- 3 Available only as complete thrust washer kit #730H01
- 4 All diffs produced before serial #17070001 came with 5mm air connection system. For information contact ARB.
- Spare axles (not supplied) will be required for vehicles with factory diff lock

LHS Axle – Ford Aust P/N: UC9P26115 RHS Axle – Ford Aust P/N: UC9P26111



^{*} Not illustrated in exploded view





RD220

T6 Ranger/BT50, RR, 32 SPL

SPECIFICATIONS

Axle Spline 32 tooth, Ø34.6mm [1.36"]

Ratio Supported Al

Ring Gear ID 141.3mm [5.56"] Ring Gear OD 226.0mm [8.90"]

Ring Gear Bolts 12 bolts on Ø168.3mm [6.63"]

Ring Gear Torque 150Nm [110 ft-lb]

Backlash 0.15-0.25mm [0.006-0.010"]

Bearing Cap Torque 75Nm [55 ft-lb]