



4X4 ACCESSORIES



DATE:

February 2010

FROM:

ARB Marketing

DESCRIPTION:

Deluxe Winch Bar

APPLICATION:

Land Rover Defender 90, 110 & 130
2009 on models

PART NO:

3432300

FITTING:

3.5 hours

AVAILABILITY DATE:

April 2010



PRODUCT SPEC SHEET

DESIGN AND DEVELOPMENT:

Featuring a large, 60.3mm diameter top tube, the 2009 on Land Rover Defender bar is a complete redesign to specifically suit the vehicle. With upswept, stepped wings that ensure approach angles are optimised and a split pan that allows maximum airflow to the engine, this bar offers more modern styling in a practical design.

Due to variations that are found in individual vehicles, the mounting system has been redesigned to enable the fitter to position the bar in the best possible place before final assembly. And although this product has been designed primarily for 2009 on models, it will also suit all Defenders models from 1985 on.

PROTECTION CHARACTERISTICS:

This bar utilises an all steel construction for maximum strength, with mandrel bent tubes to ensure even wall thickness throughout these components. The multi-fold wing section and split pan design provide the bar with a massive amount of durability, and owners can be assured that this product will provide a formidable amount of vehicle protection for the Defender.

WINCH COMPATIBILITY:

The following winches are compatible with the bull bar:

- Warn low mount models: XD9000, M10000, M12000, XP9500 & XDC9500
- Magnum low mount model: 9K

ADDITIONAL FEATURES:

- Compatible with IPF lights up to the 800 & 900 series (including Xtreme Sport & HID)
- Hi-Lift jacking points are located on either side of the centre pan
- Two CB aerial brackets are mounted on the top tube
- Recessed parking lights
- Features integrated tow points in the Hi-Lift jack recesses

Finish: durable powder coat that provides a perfect base for colour coding

INSTALLATION:

The bar is supplied with all the fixtures that are required for its successful installation. These include:

- All mounting bolts
- Parking lamps
- Detailed fitting instructions with step by step photographs
- For a list of tools that are required to perform the installation, please refer to the fitting instructions

A separate winch fitment kit is available as an optional extra containing the bracket to facilitate the mounting of the winch control box onto the bull bar, and all other necessary items.

Approximate fitting time: 3.5 hours

For more information, please refer to the fitting instructions.

The information contained in the advice was correct at the time of writing. ARB Corporation Limited and its associated companies reserve the right to alter any specification without notice. Always consult your ARB authorised distributor for the latest information on products and specifications.

PRODUCT IMAGES:



Integrated tow point in Hi-Lift jacking mount allows fitment of 4.75t bow shackle upright



Two CB aerial brackets are mounted on the top tube



Includes factory style jacking point



Close fitting design retains maximum approach angle