# AIRLOCKER ARB

## AIR OPERATED LOCKING DIFFERENTIAL

**RD131** 

## Toyota 8" IFS,50mm BRNG

PARTS L	.IST			
ITEM#	QTY	DESCRIPTION	PART#	NOTES
01	1	SEAL HOUSING O-RINGS (PK OF 2)	160207-2	1
02	1	SEAL HOUSING KIT	081806SP	
03	1	SHIM KIT	SHK009	
*	1	MASTER SHIM	150352	
04	1	BONDED SEAL	160702SP	
05	1	CLUTCH GEAR & WAVESPRING KIT	050906SP	
06	1	SPIDER BLOCK	070201SP	
07	1	LONG CROSS SHAFT	060204SP	
08	1	SIDE GEAR	SEE NOTE	2
09	1	COUNTERSUNK SCREW (PK OF 2)	200213SP	
10	1	RETAINING PIN SET (PK OF 4)	120601SP	
11	2	TAPERED ROLLER BEARING	NOT SUPPLIED	
12	1	FLANGE CAP KIT	027310SP	
13	1	WAVESPRING	150706SP	
14	1	SPLINED SIDE GEAR	SEE NOTE	2
15	2	SHORT CROSS SHAFT	060403SP	
16	4	PINION GEAR	SEE NOTE	2
17	4	PINION THRUST WASHER	SEE NOTE	3
18	2	SIDE GEAR THRUST WASHER	SEE NOTE	3
19	1	DIFFERENTIAL CASE	013010SP	
*	1	BULKHEAD FITTING KIT (BANJO TYPE)	170114	4
*	1	AIR LINE (6mm DIA X 6m LONG)	170314	4
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH FR LOCKER	180223SP	
*	1	CABLE TIE (PK OF 25)	180305	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	2102131	

\* Not illustrated in exploded view

#### **NOTES**

- 1 For replacement O-rings use only BS136 Viton 75.
- 2 Available only as complete 6 gear set # 728H111
- 3 Available only as complete thrust washer kit #730H01
- 4 All diffs produced before serial #17070001 came with 5mm air connection system. For information contact ARB.
- Spare axle retaining clips may be required (not supplied) to refit CV shafts.
- For 8" IFS with 58mm carrier bearings & 34 spline shafts refer to RD141 (Section 2.141).
- For 8" IFS with 53mm carrier bearings refer to RD111 (Section 2.111) or RD121 (Section 2.121).






## AIR OPERATED LOCKING DIFFERENTIAL

**RD131** 

Toyota 8" IFS,50mm BRNG



#### **SPECIFICATIONS**

Axle Spline 30 tooth, Ø33.0mm [1.30']

Ratio Supported

Ring Gear ID 126.0mm [4.96"] Ring Gear OD 203mm [8.0"]

Ring Gear Bolts 10 bolts on Ø160mm [6.30"]

Ring Gear Torque 96Nm [71 ft-lb]

0.13-0.18mm [0.005-0.007"] Backlash

Bearing Cap Torque 85Nm [63 ft-lb]